

Supermicro - 6029U-E series : 829U-10

| Specifications | |
|--|---|
| ENERGY STAR Partner: | Super Micro Computer, Inc. |
| Brand Name: | Supermicro |
| Model Name: | 6029U-E series |
| Model Number: | 829U-10 |
| Form Factor: | Rack-mount |
| Resilient System: | No |
| Available Expansion Slots: | 3 |
| Operating Systems Supported: | Windows |
| Power Saving Features Available: | Variable speed fan control based on power or thermal readings,Processor or core reduced power states,Low power I/O states,Power capping,Low power memory states,Dynamic voltage and frequency scaling of processor(s) |
| Product Processor Socket Count: | 2 |
| Available DIMM Slots: | 24 |
| Maximum Memory Capacity (GB): | 766.7 |
| Installed Processors for Typical or Single Configuration: | 2 |
| Cores Per Processor Typical or Single Configuration: | 12 |
| Number of Threads for Typical or Single Configuration: | 48 |
| Processor Brand Typical or Single Configuration: | Intel |
| Processor Model Name Typical or Single Configuration: | Intel(R) Xeon(R) Gold 5118 @ 2.30GHz |
| Processor Speed for Typical or Single Configuration (GHz): | 2.3 |
| Num. of DDR Channels for Typical or Single Configuration: | 2 |
| Memory Speed Typical or Single Configuration (GHz): | 2.67 |
| Typical or Single Configuration Size Per DIMM (GB): | 32 |
| Installed Num. DIMMs for Typical or Single Configuration: | 12 |
| Installed Memory for Typical or Single Configuration (GB): | 384.0 |

| Typical or Single Configuration Redundant Power Supply: | Yes |
|---|------------------|
| SERT Active State Efficiency Score Typical or Single Configuration: | 25.7 |
| SERT Version : | 2.0.1 |
| 64-bit Architecture: | 64-bit supported |
| Date Available On Market: | 2018-05-01 |
| Date Qualified: | 2019-03-06 |
| Markets: | United States |
| ENERGY STAR Certified: | Yes |

Additional Model Information

Captured On: 04/11/2021